

F100

Non Payment Terminal



Android 11



4G + 3G + 2G Wi-Fi 5: 2.4&5GHz BT 5.0



5.0" HD LCM 8MP Camera



NFC + QR







































SPECIFICATIONS

Operating System	Android 11		
Processor	Quad-Core 4*A53@2.0GHz		
Memory	RAM: 2GB + ROM: 16GB		
Communications	4G (LTE-FDD/LTE-TDD) + 3G (WCDMA) + 2G (GSM), Wi-Fi 5: 2.4&5GHz, Bluetooth 5.0/BLE		
Location	GPS/A-GPS, GLONASS, BeiDou, Galileo		
Display	5.0 inch, HD IPS LCD, 1280*720Pixel, Multi-touch		
Camera	Rear: 8MP AF with Flash		
Printer	Thermal printer, Paper size: 58mm*40mm		
Battery	3.8V/4000mAh		
Keys / Buttons	Power Key, Volume+/-Key		
Audio	1W		
NFC	13.56MHz, ISO/IEC 14443, ISO18092, Type A&B, Felica, Mifare card		
Card Slot	SIM*2 + TF Card*1		
Peripheral Ports	Type C*1(USB2.0, OTG), 3.5mm Audio Jack*1		
Power	Input: 100-240V AC, 50/60Hz 0.35A Output: 5.0V DC/2.0A		
Physical	197mm (L)*77mm (W)*52.6mm (H)		
Weight	323g		
Environment	Operating Temperature: -10°C ~ 50°C (14°F~122°F) Storage Temperature: -20°C ~ 70°C (-4°F~158°F) Relative Humidity: 5%-96% (Non-Condensing)		
Accessories	Adapter*1, USB Cable(only charging)*1, Manual*1		
Certifications	CE, ANRT, EAC, FAC, CB, BIS, WPC, DGM, UN38.3, MSDS, GSMA, Google GMS SafetyNet Compliance		
Optional Items	Card Slot SIM*1 + PSAM*1 Fingerprint Biometric fingerprint module Fiscal USB OR UART POGO PIN Connector (Type C only charging) Barcode Scann Module Image Size: 640*480 Pixels 1D&2D	USB Cable Type C (data/damping) Charging Cradle 5V/2A Multi-function Dock Lite Type C*1, RJ45*1, RJ11*1, Type A*2 Type C USB to RJ 45 Adapter 100 Mbps Ethernet LAN	Screen Protector Hydrogel film Silicone Cover Customized colors POS Bracket Desktop bracket

F100 Options and Accessories











F100 FP Fingerprint

Fingerprint	Semiconductor capacitive biometric fingerprint module	Fiscal
Physical	197mm (L)*77mm (W)*55.6mm (H)	Physical
Weight	327g	Weight

F100 Fiscal

USB OR UART POGO PIN Connector (Type C only charging)

197mm (L)*77mm (W)*52.6mm (H)

342g

Barcode Scanner

Image Size	640*480 Pixels 1D&2D
Field of View	34°(H)*27°(V)
Motion Tolerances	Up to 25in(63.5cm) per second

